

(Adopted October 15, 1993)(Amended March 10, 1995)(Amended December 7, 1995)
(Amended July 12, 1996)(Amended February 14, 1997)(Amended May 11, 2001)

**RULE 2002. ALLOCATIONS FOR OXIDES OF NITROGEN (NO_x) AND
OXIDES OF SULFUR (SO_x)**

(a) Purpose

The purpose of this rule is to establish the methodology for calculating facility Allocations for Oxides of Nitrogen (NO_x) and Oxides of Sulfur (SO_x).

(b) RECLAIM Allocations

- (1) RECLAIM Allocations will begin in 1994.
- (2) An annual Allocation will be assigned to each facility for each compliance year starting from 1994.
- (3) Allocations for each year after 2003 are equal to the facility's ending Allocation, as determined pursuant to subdivision (e) unless, as part of the AQMP process, and pursuant to Rule 2015 (b)(1), (b)(3), (b)(4), or (c), the District Governing Board determines that additional reductions are necessary to meet air quality standards, taking into consideration the current and projected state of technology available and cost-effectiveness to achieve further emission reductions.
- (4) The Facility Permit or relevant sections thereof shall be re-issued at the beginning of each compliance year to include allocations determined pursuant to subdivisions (c), (d), (e), and (f) and any RECLAIM Trading Credits (RTC) obtained pursuant to Rule 2007 - Trading Requirements for the next fifteen years thereafter and any other modifications approved or required by the Executive Officer.

(c) Establishment of Starting Allocations

- (1) The starting Allocation for RECLAIM NO_x and SO_x facilities initially permitted by the District prior to October 15, 1993, shall be determined by the Executive Officer utilizing the following methodology:

Starting Allocation= $\Sigma[A \times B_1]$ +ERCs+External Offsets

where

- A = the throughput for each NO_x and SO_x source or process unit in the facility for the maximum throughput year from 1989 to 1992 inclusive; and
- B₁ = the applicable starting emission factor for the subject source or process unit as specified in Table 1 or Table 2

- (2) (A) Use of 1992 data is subject to verification and revision by the Executive Officer or designee to assure validity and accuracy.
- (B) The maximum throughput year will be determined by the Executive Officer or designee from throughput data reported through annual emissions reports submitted pursuant to Rule 301 - Permit Fees, or may be designated by the permit holder prior to issuance of the Facility Permit.
- (C) To determine the applicable starting emission factor in Table 1 or Table 2, the Executive Officer or designee will categorize the equipment at each facility based on information relative to hours of operation, equipment size, heating capacity, and permit information submitted pursuant to Rule 201 - Permit to Construct, and other relevant parameters as determined by the Executive Officer or designee. No information used for purposes of this subparagraph may be inconsistent with any information or statement previously submitted on behalf of the facility to the District, including but not limited to information and statements previously submitted pursuant to Rule 301 - Permit Fees, unless the facility can demonstrate, by clear and convincing documentation, that such information or statement was inaccurate.
- (D) Throughput associated with each piece of equipment or NO_x or SO_x source will be multiplied by the starting emission factors specified in Table 1 or Table 2. If a lower emission factor was utilized for a given piece of equipment or NO_x or SO_x source pursuant to Rule 301 - Permit Fees, than the factor in Table 1 or Table 2, the lower factor will be used for determining that portion of the Allocation.

- (E) Fuel heating values may be used to convert throughput records into the appropriate units for determining Allocations based on the emission factors in Table 1 or Table 2. If a different unit basis than set forth in Tables 1 and 2 is needed for emissions calculations, the Executive Officer shall use a default heating value to determine source emissions, unless the Facility Permit holder can demonstrate with substantial evidence to the Executive Officer that a different value should be used to determine emissions from that source.
- (3) All NO_x and SO_x ERCs held by a RECLAIM Facility Permit holder shall be reissued as RTCs. RECLAIM facilities will have these RTCs added to their starting Allocations. RTCs generated from the conversion of ERCs shall have a zero rate of reduction for the year 1994 through the year 2000. Such RTCs shall have a cumulative rate of reduction for the years 2001, 2002, and 2003, equal to the percentage inventory adjustment factor applied to 2003 Allocations pursuant to paragraph (e)(1) of this rule.
- (4) Non-RECLAIM facilities may elect to have their ERCs converted to RTCs and listed on the RTC Listing maintained by the Executive Officer or designee pursuant to Rule 2007 - Trading Requirements, so long as the written request is filed before July 1, 1994. Such RTCs will be assigned to the trading zone in which the generating facility is located. RTCs generated from the conversion of ERCs shall have a zero rate of reduction for the year 1994 through the year 2000. Such RTCs shall have a cumulative rate of reduction for the years, 2001, 2002, and 2003, equal to the percentage inventory adjustment factor applied to 2003 Allocations pursuant to paragraph (e)(1) of this rule.
- (5) External offsets provided pursuant to Regulation XIII - New Source Review, not including any offsets in excess of a 1 to 1 ratio, will be added to the starting Allocation pursuant to paragraph (c)(1) provided:
 - (A) The offsets were not received from either the Community Bank or the Priority Reserve.
 - (B) External offsets will only be added to the starting Allocation to the extent that the Facility Permit holder demonstrates that they have not already been included in the starting Allocation or as an ERC.

RTCs issued for external offsets shall not include any offsets in excess of a 1 to 1 ratio required under Regulation XIII - New Source Review.

- (C) RTCs generated from the conversion of external offsets shall have a zero rate of reduction for the year 1994 through the year 2000. These RTCs shall have a cumulative rate of reduction for the years 2001, 2002, and 2003, equal to the percentage inventory adjustment factor applied to 2003 Allocations pursuant to paragraph (e)(1) of this rule.
 - (D) Existing facilities with units that have Permits to Construct issued pursuant to Regulation II - Permits, dated on or after January 1, 1992, or existing facilities which have, between January 1, 1992 and October 15, 1993, installed air pollution control equipment that was exempt from offset requirements pursuant to Rule 1304 (a)(5), shall have their starting Allocations increased by the total external offsets provided, or the amount that would have been offset if the exemption had not applied.
 - (E) Existing facilities with units whose reported emissions are below capacity due to phased construction, and/or where the Permit to Operate issued pursuant to Regulation II - Permits, was issued after January 1, 1992, shall have their starting Allocations increased by the total external offsets provided.
- (6) If a Facility Permit holder can demonstrate that its 1994 Allocation is less than the 1992 emissions reported pursuant to Rule 301 - Permit Fees, and that the facility was, in 1992, operating in compliance with all applicable District rules in effect as of December 31, 1993, the facility's starting Allocation will be equal to the 1992 reported emissions.
 - (7) For new facilities initially totally permitted on or after January 1, 1993 but prior to October 15, 1993, the starting Allocation shall be equal to the external offsets provided by the facility to offset emission increases at the facility pursuant to Regulation XIII - New Source Review, not including any offsets in excess of a 1 to 1 ratio.
 - (8) The Allocation for new facilities initially totally permitted on and after October 15, 1993, shall be equal to the total RTCs provided by the facility to offset emission increases at the facility pursuant to Rule 2005- New Source Review for RECLAIM.

- (9) The starting Allocation for facilities which enter the RECLAIM program pursuant to Rule 2001 - Applicability, shall be determined by the methodology in paragraph (c)(1) of this rule. The most recent two years reported emission fee data filed pursuant to Rule 301 - Permit Fees, may be used if 1989 through 1992 emission fee data is not available. For facilities lacking reported emission fee data, the Allocation shall be equal to the external offsets provided pursuant to Regulation XIII - New Source Review, not including any offsets in excess of a 1 to 1 ratio. The Allocation shall not include any emission offsets received from either the Community Bank or the Priority Reserve.
- (10) A facility may not receive more than one set of Allocations.
- (11) A facility that is no longer holding a valid District permit on January 1, 1994 will not receive an Allocation, but may, if authorized by Regulation XIII, apply for ERCs.
- (12) Clean Fuel Adjustment to Starting Allocation
Any refiner who is required to make modifications to comply with CARB Phase II reformulated gasoline production (California Code of Regulations, Title 13, Sections 2250, 2251.5, 2252, 2260, 2261, 2262, 2262.2, 2262.3, 2262.4, 2262.5, 2262.6, 2262.7, 2263, 2264, 2266, 2267, 2268, 2269, 2270, and 2271) or federal requirements (Federal Clean Air Act, Title II, Part A, Section 211; 42 U.S.C. Section 7545) may receive (an) increase(s) in his Allocations except to the extent that there is an increase in maximum rating of the new or modified equipment. Each facility requesting an increase to Allocations shall submit an application for permit amendment specifying the necessary modifications and tentative schedule for completion. The Facility Permit holder shall establish the amount of emission increases resulting from the reformulated gasoline modifications for each year in which the increase in Allocations is requested. The increase to its Allocations will be issued contemporaneously with the modification according to a schedule approved by the Executive Officer or designee (i.e., 1994 through 1997 depending on the refinery). Each increase to the Allocations shall be equal to the increased emissions resulting from the modifications solely to comply with the state or federal reformulated gasoline requirements at the refinery or facility producing hydrogen for reformulated gasoline

production, and shall be established according to present and future compliance limits in current District rules or permits. Allocation increases for each refiner pursuant to this paragraph, shall not exceed 5 percent of the refiner's total starting Allocation, unless any refiner emits less than 0.0135 tons of NO_x per thousand barrels of crude processed, in which case the Allocation increases for such refiner shall not exceed 20 percent of that refiner's starting Allocation. The emissions per amount of crude processed will be determined on the basis of information reported to the District pursuant to Rule 301 - Permit Fees, for the same calendar year as the facility's peak activity year for their NO_x starting Allocation.

(d) Establishment of Year 2000 Allocations

- (1) (A) The year 2000 Allocations for RECLAIM NO_x and SO_x facilities will be determined by the Executive Officer or designee utilizing the following methodology:

$$\text{Year 2000 Allocation} = \sum [A \times B_2] + \text{RTCs created from ERCs + External Offsets,}$$

where

A = the throughput for each NO_x or SO_x source or process unit in the facility for the maximum throughput year from 1987 to 1992, inclusive, as reported pursuant to Rule 301 - Permit Fees; and

B₂ = the applicable Tier I year Allocation emission factor for the subject source or process unit, as specified in Table 1 or Table 2.

- (B) The maximum throughput year will be determined by the Executive Officer or designee from throughput data reported through annual emissions reports pursuant to Rule 301 - Permit Fees, or may be designated by the permit holder prior to issuance of the Facility Permit.
- (C) To determine the applicable emission factor in Table 1 or Table 2, the Executive Officer or designee will categorize the equipment at each facility based on information on hours of operation, equipment size, heating capacity, and permit information submitted pursuant to Rule 201 - Permit to Construct, and other parameters as determined by the Executive Officer or designee.

No information used for purposes of this subparagraph may be inconsistent with any information or statement previously submitted on behalf of the facility to the District including but not limited to information and statements previously submitted pursuant to Rule 301 - Permit Fees, unless the facility can demonstrate, by clear and convincing documentation, that such information or statement was inaccurate.

- (D) Throughput associated with each piece of equipment or NO_x or SO_x source will be multiplied by the Tier I emission factor specified in Table 1 or Table 2. If a factor lower than the factor in Table 1 or Table 2 was utilized for a given piece of equipment or NO_x or SO_x source pursuant to Rule 301, the lower factor will be used for determining that portion of the Allocation.
 - (E) The fuel heating value may be considered in determining Allocations and will be set to 1.0 unless the Facility Permit holder demonstrates that it should receive a different value.
 - (F) The year 2000 Allocation is the sum of the resulting products for each piece of equipment or NO_x or SO_x source multiplied by any inventory adjustment pursuant to paragraph (d)(4) of this rule.
- (2) For facilities existing prior to October 15, 1993 which enter RECLAIM after October 15, 1993, the year 2000 Allocation will be determined according to paragraph (d)(1). The most recent two years reported emission fee data filed pursuant to Rule 301 - Permit Fees, may be used if 1989 through 1992 emission fee data is not available. For facilities lacking reported emission fee data, the Allocation shall be equal to their external offsets provided pursuant to Regulation XIII - New Source Review, not including any offsets in excess of a 1 to 1 ratio.
 - (3) No facility shall have a year 2000 Allocation [calculated pursuant to subdivision (d)] greater than the starting Allocation [calculated pursuant to subdivision (c)].
 - (4) If the sum of all RECLAIM facilities' year 2000 Allocations differs from the year 2000 projected inventory for these sources under the 1991 AQMP, the Executive Officer or designee will establish a percentage inventory adjustment factor that will be applied to adjust each facility's year 2000 Allocation. The inventory adjustment will not apply to RTCs generated from ERCs or external offsets.

- (e) Allocations for the Year 2003
 - (1) The 2003 Allocations will be determined by the Executive Officer or designee applying a percentage inventory adjustment to reduce each facility's unadjusted year 2000 Allocation so that the sum of all RECLAIM facilities' 2003 Allocations will equal the 1991 AQMP projected inventory for RECLAIM sources for the year 2003, corrected based on actual facility data reviewed for purposes of issuing Facility Permits and to reflect the highest year of actual Basin-wide economic activity for RECLAIM sources considered as a whole during the years 1987 through 1992.
 - (2) No facility shall have a 2003 Allocation (calculated pursuant this subdivision) greater than the year 2000 Allocation [calculated pursuant to subdivision (d)].
- (f) Annual Allocations for NO_x and SO_x
 - (1) Allocations for the years between 1994 and 2000, for RECLAIM NO_x and SO_x facilities shall be determined by a straight line rate of reduction between the starting Allocation and the year 2000 Allocation. For the years 2001 and 2002, the Allocations shall be determined by a straight line rate of reduction between the year 2000 and year 2003 Allocations. Allocations for each year after 2003 are equal to the facility's ending Allocation, as determined pursuant to subdivision (e) , unless as part of the AQMP process, and pursuant to Rule 2015 (b)(1), (b)(3), (b)(4), or (c), the District Governing Board determines that additional reductions are necessary to meet air quality standards, taking into consideration the current and projected state of technology available and cost-effectiveness to achieve further emission reductions.
 - (2) New facilities initially totally permitted, on and after October 15, 1993, shall not have a rate of reduction. The Facility Permit for such facilities will require the Facility Permit holder to, at the commencement of each compliance year, hold RTCs equal to the amount of RTCs provided as offsets pursuant to Rule 2005.
 - (3) Increases to Allocations for permits issued for Clean Fuel adjustments pursuant to paragraph (c)(12), shall be added to each year's Allocation.

(g) High Employment/Low Emissions (HILO) Facility

The Executive Officer or designee will establish a HILO bank funded with the following maximum total annual emission Allocations:

- (1) 91 tons per year of NO_x
- (2) 91 tons per year of SO_x
- (3) After January 1, 1997, new facilities may apply to the HILO bank in order to obtain non-tradeable RTCs. Requests will be processed on a first-come, first-served basis, pending qualification.
- (4) When credits are available, annual Allocations will be granted for the year of application and all subsequent years.
- (5) HILO facilities receiving such Allocations from the HILO bank must verify their HILO status on an annual basis through their APEP report.
- (6) Failure to qualify will result in all subsequent years' credits being returned to the HILO bank.
- (7) Facilities failing to qualify for the HILO bank Allocations may reapply at any time during the next or subsequent compliance year when credits are available.

(h) Non-Tradeable Allocation Credits

- (1) Any existing RECLAIM facility with reported emissions pursuant to Rule 301 - Permit Fees, in either 1987, 1988, or 1993, greater than its starting Allocation, shall be assigned non-tradeable credits for the first three years of the program which shall be determined according to the following methodology:

Non-tradeable credit for NO_x and SO_x:

Year 1 = $(\Sigma [A \times B_1]) - 1994 \text{ Allocation};$

Where:

A = the throughput for each NO_x or SO_x source or process unit in the facility from the single maximum throughput year from 1987, 1988, or 1993; and

B₁ = the applicable starting emission factor, as specified in Table 1 or Table 2.

Year 2 = Year 1 non-tradeable credits X 0.667

Year 3 = Year 1 non-tradeable credits X 0.333

Year 4 and subsequent years = Zero non-tradeable credit.

- (2) The use of non-tradeable credits shall be subject to the following requirements:
- (A) Non-tradeable credits may only be used for an increase in throughput over that used to determine the facility's starting Allocation. Non-tradeable credits may not be used for emissions increases associated with equipment modifications, change in feedstock or raw materials, or any other changes except increases in throughput. The Executive Officer or designee may impose Facility Permit conditions necessary to ensure compliance with this subparagraph.
 - (B) The use of activated non-tradeable credits shall be subject to a non-tradeable RTC mitigation fee, as specified in Rule 301 subdivision (n).
 - (C) In order to utilize non-tradeable credits, the Facility Permit holder shall submit a request to the Executive Officer or designee in writing, including a demonstration that the use of the non-tradeable credits complies with all requirements of this paragraph, pay any fees required pursuant to Rule 301 - Fees, and have received written approval from the Executive Officer or designee for their use. The Executive Officer or designee shall deny the request unless the Facility Permit holder demonstrates compliance with all requirements of this paragraph. The Executive Officer or designee shall, in writing, approve or deny the request within three business days of submittal of a complete request and notify the Facility Permit holder of the decision. If the request is denied, the Executive Officer or designee will refund the mitigation fee.
 - (D) In the event that a facility transfers any RTCs for the year in which non-tradeable credits have been issued, the non-tradeable credit Allocation shall be invalid, and is no longer available to the facility.

Table 1

RECLAIM NO_x Emission Factors

Nitrogen Oxides Basic Equipment	Fuel	"Throughput " Units	Starting Ems Factor *	Ending Ems Factor *
Afterburner (Direct Flame and Catalytic)	Natural Gas	mmcf	130.000	39.000
Afterburner (Direct Flame and Catalytic)	LPG, Propane, Butane	1000 Gal	RV	3.840
Afterburner (Direct Flame and Catalytic)	Diesel	1000 Gal	RV	5.700
Agr Chem-Nitric Acid	Process-Absrbr Tailgas/Nw	tons pure acid produced	RV	1.440
Agricultural Chem - Ammonia	Process	tons produced	RV	1.650
Air Ground Turbines	Air Ground Turbines	(unknown process units)	RV	1.860
Ammonia Plant	Neutralizer Fert, Ammon Nit	tons produced	RV	2.500
Asphalt Heater, Concrete	Natural Gas	mmcf	130.000	65.000
Asphalt Heater, Concrete	Fuel Oil	1000 gals	RV	9.500
Asphalt Heater, Concrete	LPG	1000 gals	RV	6.400
Boiler, Heater R1109 (Petr Refin)	Natural Gas	mmbtu	0.100	0.030
Boiler, Heater R1109 (Petr Refin)	Fuel Oil	mmbtu	0.100	0.030
Boiler, Heater R1146 (Petr Refin)	Natural Gas	mmbtu	0.045	0.045
Boiler, Heater R1146 (Petr Refin)	Fuel Oil	mmbtu	0.045	0.045
Boiler, Heater R1146 (Petr Refin)	Refinery Gas	mmbtu	0.045	0.045
Boilers, Heaters, Steam Gens Rule 1146 and 1146.1	Natural Gas	mmcf	49.180	47.570
Boilers, Heaters, Steam Gens Rule 1146 and 1146.1	LPG, Propane, Butane	1000 gals	4.400	4.260
Boilers, Heaters, Steam Gens Rule 1146 and 1146.1	Diesel Light Dist. (0.05% S)	1000 gals	6.420	6.210
Boilers, Heaters, Steam Gens Rule 1146 and 1146.1	Refinery Gas	mmcf	51.520	49.840
Boilers, Heaters, Steam Gens	Bituminous Coal	tons burned	RV	4.800
Boiler, Heater, Steam Gen (Rule 1146.1)	Natural Gas	mmcf	130.000	39.460
Boiler, Heater, Steam Gen (Rule 1146.1)	Refinery Gas	mmcf	RV	41.340

* RV = Reported Value

** Does not include ceramic, clay, cement or brick kilns or metal melting, heat treating or glass melting furnaces.

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.

Nitrogen Oxides Basic Equipment	Fuel	"Throughput" Units	Starting Ems Factor *	Ending Ems Factor *
Boiler, Heater, Steam Gen (Rule 1146.1)	LPG, Propane, Butane	1000 gallons	RV	3.530
Boiler, Heater, Steam Gen (Rule 1146.1)	Diesel Light Dist (0.05%)	1000 gallons	RV	5.150
Boiler, Heater, Steam Gen (Rule 1146)	Natural Gas	mmcf	47.750	47.750
Boiler, Heater, Steam Gen (Rule 1146)	Refinery Gas	mmcf	50.030	50.030
Boiler, Heater, Steam Gen (Rule 1146)	LPG, Propane, Butane	1000 gallons	4.280	4.280
Boiler, Heater, Steam Gen (Rule 1146)	Diesel Light Dist (0.05%)	1000 gallons	6.230	6.230
Boiler, Heater, Steam Gen (R1146, <90,000 Therms)	Natural Gas	mmcf	RV	47.750
Boiler, Heater, Steam Gen (R1146, <90,000 Therms)	Refinery Gas	mmcf	RV	50.030
Boiler, Heater, Steam Gen (R1146, <90,000 Therms)	LPG, Propane, Butane	1000 gallons	RV	4.280
Boiler, Heater, Steam Gen (R1146, <90,000 Therms)	Diesel Light Dist (0.05%)	1000 gallons	RV	6.230
Boiler, Heater, Steam Gen (R1146.1, <18,000 Therms)	Natural Gas	mmcf	RV	39.460
Boiler, Heater, Steam Gen (R1146.1, <18,000 Therms)	Refinery Gas	mmcf	RV	41.340
Boiler, Heater, Steam Gen (R1146.1, <18,000 Therms)	LPG, Propane, Butane	1000 gallons	RV	3.530
Boiler, Heater, Steam Gen (R1146.1, <18,000 Therms)	Diesel Light Dist (0.05%)	1000 gallons	RV	5.150
Boiler, Heater R1109 (Petr Refin)	Refinery Gas	mmbtu	0.100	0.030
Boilers, Heaters, Steam Gens, (Petr Refin)	Natural Gas	mmcf	105.000	31.500
Boilers, Heaters, Steam Gens, (Petr Refin)	Refinery Gas	mmcf	110.000	33.000
Boilers, Heaters, Steam Gens, Unpermitted	Natural Gas	mmcf	130.000	32.500
Boilers, Heaters, Steam Gens, Unpermitted	LPG, Propane, Butane	1000 gallons	RV	3.200
Boilers, Heaters, Steam Gens (New or Modified, and subject to BACT, after the start year as determined pursuant to Rule 2002(c)(1))	Natural Gas	mmcf	38.460	38.460

* RV = Reported Value

** Does not include ceramic, clay, cement or brick kilns or metal melting, heat treating or glass melting furnaces.

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.

Nitrogen Oxides Basic Equipment	Fuel	"Throughput" Units	Starting Ems Factor *	Ending Ems Factor *
Boilers, Heaters, Steam Gens (New or Modified, and subject to BACT, after the start year as determined pursuant to Rule 2002(c)(1))	Refinery Gas	mmbtu	0.035	0.035
Boilers, Heaters, Steam Gens (New or Modified, and subject to BACT, after the start year as determined pursuant to Rule 2002(c)(1))	LPG, Propane, Butane	1000 gallons	3.55	3.55
Boilers, Heaters, Steam Gens (New or Modified, and subject to BACT, after the start year as determined pursuant to Rule 2002(c)(1))	Diesel Light Dist (0.05%), Fuel Oil No. 2	mmbtu	0.03847	0.03847
Boilers, Heaters, Steam Gens, Unpermitted	Diesel Light Dist (0.05%)	1000 gallons	RV	4.750
Catalyst Manufacturing	Catalyst Mfg	tons of catalyst produced	RV	1.660
Catalyst Manufacturing	Catalyst Mfg	tons of catalyst produced	RV	2.090
Cement Kilns	Natural Gas	mmcf	130.000	19.500
Cement Kilns	Diesel Light Dist. (0.05% S)	1000 gals	RV	2.850
Cement Kilns	Kilns-Dry Process	tons cement produced	RV	0.750
Cement Kilns	Bituminous Coal	tons burned	RV	4.800
Cement Kilns	Tons Clinker	tons clinker	RV	2.73***
Ceramic and Brick Kilns (Preheated Combustion Air)	Natural Gas	mmcf	213.000	170.400
Ceramic and Brick Kilns (Preheated Combustion Air)	Diesel Light Distillate (.05%)	1000 gallons	RV	24.905
Ceramic and Brick Kilns (Preheated Combustion Air)	LPG	1000 gallons	RV	16.778
Ceramic Clay Mfg	Drying	tons input to process	RV	1.114
CO Boiler	Refinery Gas	mmbtu		0.030
Cogen, Industr	Coke	tons burned	RV	3.682
Electric Generation, Commercial Institutional Boiler	Distillate Oil	1000 gallons	6.420	6.210
Composite Internal Combustion	Waste Fuel Oil	1000 gals burned	RV	31.340
Curing and Drying Ovens	Natural Gas	mmcf	130.000	32.500

* RV = Reported Value

** Does not include ceramic, clay, cement or brickkilns or metal melting, heat treating or glass melting furnaces.

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.

Nitrogen Oxides Basic Equipment	Fuel	"Throughput" Units	Starting Ems Factor *	Ending Ems Factor *
Curing and Drying Ovens	LPG, Propane, Butane	1000 gals	RV	3.200
Delacquering Furnace	Natural Gas	mmcf	182.2***	182.2***
Fiberglass	Textile-Type Fibr	tons of material processed	RV	1.860
Fluid Catalytic Cracking Unit	Fresh Feed	1000 BBLS fresh feed	RV	RV*0.3 ***
Fluid Catalytic Cracking Unit with Urea Injection	Fresh Feed	1000 BBLS fresh feed	RV	(RV*0.3) / (1-control efficiency) ***
Fugitive Emission	Not Classified	tons product	RV	0.087
Furnace Process	Carbon Black	tons produced	RV	38.850
Furnace Suppressor	Furnace Suppressor	unknown	RV	0.800
Glass Fiber Furnace	Mineral Products	tons product produced	RV	4.000
Glass Melting Furnace	Flat Glass	tons of glass pulled	RV	4.000
Glass Melting Furnace	Tableware Glass	tons of glass pulled	RV	5.680
Glass Melting Furnaces	Container Glass	tons of glass produced	4.000	1.2***
ICEs, Permitted (Rule 1110.1 and 1110.2)	Natural Gas	mmcf	2192.450	217.360
ICEs Permitted (Rule 1110.2)	Natural Gas	mmcf	RV	217.360
ICEs, Permitted (Rule 1110.1 and 1110.2)	LPG, Propane, Butane	1000 gals	RV	19.460
ICEs, Permitted (Rule 1110.1 and 1110.2)	Gasoline	1000 gals	RV	20.130
ICEs, Permitted (Rule 1110.1 and 1110.2)	Diesel Oil	1000 gals	RV	31.340
ICEs, Exempted per Rule 1110.2	All Fuels		RV	RV
ICEs, Exempted per Rule 1110.2 and subject to Rule 1110.1	All Fuels		RV	RV
ICEs, Unpermitted	All Fuels		RV	RV
In Process Fuel	Coke	tons burned	RV	24.593
Incinerators	Natural Gas	mmcf	130.000	104.000
Industrial	Propane	1000 gallons	RV	20.890
Industrial	Gasoline	1000 gallons	RV	21.620
Industrial	Dist.Oil/Diesel	1000 gallons	RV	33.650
Inorganic Chemicals, H2SO4 Chamber	General	tons pure acid produced	RV	0.266

* RV = Reported Value

** Does not include ceramic, clay, cement or brick kilns or metal melting, heat treating or glass melting furnaces.

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.

Nitrogen Oxides Basic Equipment	Fuel	"Throughput" Units	Starting Ems Factor*	Ending Ems Factor *
Inorganic Chemicals, H2SO4 Contact	Absrbr 98.0% Conv	tons 100% H2SO4	RV	0.376
Iron/Steel Foundry	Steel Foundry, Elec Arc Furn	tons metal processed	RV	0.045
Metal Heat Treating Furnace	Natural Gas	mmcf	130.000	104.000
Metal Heat Treating Furnace	Diesel Light Distillate (.05%)	1000 gallons	RV	15.200
Metal Heat Treating Furnace	LPG	1000 gallons	RV	10.240
Metal Forging Furnace (Preheated Combustion Air)	Natural Gas	mmcf	213.000	170.400
Metal Forging Furnace (Preheated Combustion Air)	Diesel Light Distillate (.05%)	1000 gallons	RV	24.905
Metal Forging Furnace (Preheated Combustion Air)	LPG	1000 gallons	RV	16.778
Metal Melting Furnaces	Natural Gas	mmcf	130.000	65.000
Metal Melting Furnaces	LPG, Propane, Butane	1000 gals	RV	6.400
Miscellaneous		bbls-processed	RV	1.240
Natural Gas Production	Not Classified	mmcf gas	RV	6.320
Nonmetallic Mineral	Sand/Gravel	tons product	RV	0.030
NSPS	Refinery Gas	mmbtu	RV	0.030
Other Bact Heater (24F-1)	Natural Gas	mmcf	RV	RV
Other Heater (24F-1)	Pressure Swing Absorber Gas	mmcf	RV	RV
Ovens, Kilns, Calciners, Dryers, Furnaces**	Natural Gas	mmcf	130.000	65.000
Ovens, Kilns, Calciners, Dryers, Furnaces**	Diesel Light Dist. (0.05% S)	1000 gals	RV	9.500
Paint Mfg, Solvent Loss	Mixing/Blending	tons solvent	RV	45.600
Petroleum Refining	Asphalt Blowing	tons of asphalt produced	RV	45.600
Petroleum Refining, Calclner	Petroleum Coke	Calcined Coke	RV	0.971***
Plastics Prodn	Polyester Resins	tons product	RV	106.500
Pot Furnace	Lead Battery	lbs Niter	0.077***	0.062***
Process Specific	ID# 012183	(unknown process units)	RV	240.000
Process Specific	SCC 30500311	tons produced	RV	0.140

* RV = Reported Value

** Does not include ceramic, clay, cement or brick kilns or metal melting, heat treating or glass melting furnaces.

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.

Nitrogen Oxides Basic Equipment	Fuel	"Throughput" Units	Starting Ems Factor*	Ending Ems Factor *
Process Specific	ID 14944	(unknown process units)	RV	0.512
SCC 39090003			RV	170.400
Sec. Aluminum	Sweating Furnace	tons produced	RV	0.300
Sec. Aluminum	Smelting Furnace	tons metal produced	RV	0.323
Sec. Aluminum	Annealing Furnace	mmcf	130.000	65.000
Sec. Aluminum	Boring Dryer	tons produced	RV	0.057
Sec. Lead	Smelting Furnace	tons metal charged	RV	0.110
Sec. Lead	Smelting Furnace	tons metal charged	RV	0.060
Sodium Silicate Furnace	Water Glass	Tons Glass Pulled	RV	6.400
Steel Hot Plate Furnace	Natural Gas	mmcf	213.000	106.500
Steel Hot Plate Furnace	Diesel Light Distillate (.05%)	1000 gallons	31.131	10.486
Steel Hot Plate Furnace	LPG, Propane, Butane	1000 gallons	20.970	10.486
Surface Coal Mine	Haul Road	tons coal	RV	62.140
Tail Gas Unit		hours of operation	RV	RV
Turbines	Butane	1000 Gallons	RV	5.700
Turbines	Diesel Oil	1000 gals	RV	8.814
Turbines	Refinery Gas	mmcf	RV	62.275
Turbines	Natural Gas	mmcf	RV	61.450
Turbines - Peaking Unit	Natural Gas	mmcf	RV	RV
Turbines - Peaking Unit	Dist. Oil/Diesel	1000 gallons	RV	RV
Utility Boiler	Digester/Landfill Gas	mmcf	52.350	10.080
Turbine	Natural Gas	mmcf	RV	61.450
Turbine	Fuel Oil	1000 gallons	RV	8.810
Turbine	Dist.Oil/Diesel	1000 gallons	RV	3.000
Utility Boiler Burbank	Natural Gas	mmcf	148.670	17.200
Utility Boiler Burbank	Residual Oil	1000 gallons	20.170	2.330
Utility Boiler, Glendale	Natural Gas	mmcf	140.430	16.000
Utility Boiler, Glendale	Residual Oil	1000 gallons	20.160	2.290
Utility Boiler, LADWP	Natural Gas	mmcf	86.560	15.830
Utility Boiler, LADWP	Residual Oil	1000 gallons	12.370	2.260
Utility Boiler, LADWP	Digester Gas	mmcf	52.350	10.080
Utility Boiler, LADWP	Landfill Gas	mmcf	37.760	6.910
Utility Boiler, Pasadena	Natural Gas	mmcf	195.640	18.500
Utility Boiler, Pasadena	Residual Oil	1000 gallons	28.290	2.670
Utility Boiler, SCE	Natural Gas	mmcf	74.860	15.600
Utility Boiler, SCE	Residual Oil	1000 gallons	10.750	2.240

* RV = Reported Value

** Does not include ceramic, clay, cement or brick kilns or metal melting, heat treating or glass melting furnaces.

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.

Table 2

RECLAIM SO_x Emission Factors

Sulfur Oxides Basic Equipment	Fuel	"Throughput" Units	Starting Emission Factor *	Ending Emission Factor *
Air Blown Asphalt		hours of operation	RV	RV
Asphalt Concrete	Cold Ag Handling	tons produced	RV	0.032
Calcliner	Petroleum Coke	Calcined Coke	RV	0.000
Catalyst Regeneration		hours of operation	RV	RV
Cement Kiln	Distillate Oil	1000 gallons	RV	RV
Cement Mfg	Kilns, Dry Process	tons produced	RV	RV
Claus Unit		pounds	RV	RV
Cogen	Coke	pounds per ton	RV	RV
Non Fuel Use		hours of operation	RV	RV
External Combustion Equipment / Incinerator	Natural Gas	mmcf	RV	0.830
External Combustion Equip/Incinerator	LPG, Propane, Butane	1000 gallons	RV	4.600
External Combustion Equip/Incinerator	Diesel Light Dist. (0.05% S)	1000 gallons	7.00	5.600
External Combustion Equip/Incinerator	Residual Oil	1000 gallons	8.00	6.400
External Combustion Equip/Incinerator	Refinery Gas	mmcf	RV	6.760
Fiberglass	Recuperative Furn, Textile-Type Fiber	tons produced	RV	2.145
Fluid Catalytic Cracking Units		1000 bbls refinery feed	RV	13.700
Glass Mfg, Forming/Fin	Container Glass		RV	RV
Grain Milling	Flour Mill	tons Grain Processed	RV	RV
ICEs	Natural Gas	mmcf	RV	0.600
ICEs	LPG, Propane, Butane	1000 gallons	RV	0.350
ICEs	Gasoline	1000 gallons	RV	4.240
ICEs	Diesel Oil	1000 gallons	6.24	4.990
Industrial	Cogeneration, Bituminous Coal	tons produced	RV	RV
Industrial (scc 10200804)	Cogeneration, Coke	tons produced	RV	RV
Inorganic Chemicals	General, H ₂ SO ₄ Chamber	tons produced	RV	RV
Inorganic Chemicals	Absrbr 98.0% Conv, H ₂ SO ₄ Contact	tons produced	RV	RV

* RV = Reported Value

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.

Sulfur Oxides Basic Equipment	Fuel	"Throughput" Units	Starting Emission Factor *	Ending Emission Factor *
Inprocess Fuel	Cement Kiln/Dryer, Bituminous Coal	tons produced	RV	RV
Iron/Steel Foundry	Cupola, Gray Iron Foundry	tons produced	RV	0.720
Melting Furnace, Container Glass		tons produced	RV	RV
Mericher Alkyd Feed		hours of operation	RV	RV
Miscellaneous	Not Classified	tons produced	RV	0.080
Miscellaneous	Not Classified	tons produced	RV	0.399
Natural Gas Production	Not Classified	mmcf	RV	527.641
Organic Chemical (scc 30100601)		tons produced	RV	RV
Petroleum Refining (scc30600602)	Column Condenser		RV	1.557
Petroleum Refining (scc30600603)	Column Condenser		RV	1.176
Refinery Process Heaters	LPG fired	1000 gal	RV	2.259
Pot Furnace	Lead Battery	lbs Sulfur	0.133***	0.106***
Sec. Lead	Reverberatory, Smelting Furnace	tons produced	RV	RV
Sec. Lead	Smelting Furnace, Fugitiv	tons produced	RV	0.648
Sour Water Oxidizer		hours of operation	RV	RV
Sulfur Loading		1000 bbls	RV	RV
Sour Water Oxidizer		1000 bbls fresh feed	RV	RV
Sour Water Coker		1000 bbls fresh feed	RV	RV
Sodium Silicate Furnace		tons of glass pulled	RV	RV
Sulfur Plant		hours of operation	RV	RV
Tail gas unit		hours of operation	RV	RV
Turbines	Refinery Gas	mmcf	RV	6.760
Turbines	Natural Gas	mmcf	RV	0.600
Turbines	Diesel Oil	1000 gal	6.24	0.080
Turbines	Residual Oil	1000 gallons	8.00	0.090
Utility Boilers	Diesel Light Dist. (0.05% S)	1000 gallons	7.00	0.080
Utility Boilers	Residual Oil	1000 gallons	8.00	0.090
Other Heater (24F-1)	Pressure Swing Absorber Gas	mmcf	RV	RV

* RV = Reported Value

*** Applies retroactively to January 1, 1994 for Cycle 1 facilities and July 1, 1994 for Cycle 2 facilities.